


Emergency Eye Wash With Pedal 380



Description

- Picker eyewash green polypropylene.
- Built in galvanized steel coated with epoxy paint.
- Equipment Emergency eyewash high flow at low pressure with full bore valve, automatic opening and closing instant manual actuation by side lever and pedal.
- Suitable for industries, workshops, laboratories and generally where there is risk to personnel from fire damage, acid reagents, petroleum products, radioactive materials or other contaminant.
- Brass Connectors.
- minimum supply pressure 1.5 bar water - up to 5 bar.
- Water flow rate: 14 l / min $\pm$ 10%.
- Water inlet: Thread 1/2 ".
- Water outlet: thread 1 + 1/4 ".

BOCCHI emergency showers and eyewashes fully comply with the specifications

Features

Marca

Categoria

Portable
washer eyes

Price

Price 295,20 €

Without VAT 240,00 €

Product in Store

[Emergency Eye Wash With Pedal 380](#)

requirements of the regulations:

- EN 15154-1 Standards for shower devices for the body connected to the water network and according to which the minimum flow rate of the sprayer Must be at least 100 l / min. Emergency showers DILUVIO a flow rate greater than 120 l / min at 0.3 MPa.
- EN 15154-2 Standards for eyewash units connected to the water mains and according to which the minimum flow rate of the eyewash must be at least 6 l / min. DILUVIO eye drops have a flow rate of over 14 l/min at 0.3 MPa.
- UNI9608 regulations governing the use of showers and eyewashes
- Emergency
- UNI10271 Regulations governing the use of eyewash / laptop washers
- UNI7546 / 2 UNI7546 / 3 UNI7546 / 4 which requires the presence of an individual captive cartel for the shower and another for the emergency eyewash.
- Din 12899 PART 2
- ANSI Z358.1-2004 (American National Sanitation Institute).

Documents

[Technical Data Sheets - ES \(177.38 Kb\)](#)

[Technical Data Sheets - ES \(116.76 Kb\)](#)

[Installation Guide - PT \(105.56 Kb\)](#)

[Certificates - CE \(288.5 Kb\)](#)