

Emergency Shower, Horizontal, With Manual



Description

- Horizontal emergency shower for wall mounting.
- Full bore valve, the opening and closing instant automatic manual.
- Rigid rod with triangular handle.
- Spray green polypropylene.
- Constructed from galvanized steel coated with epoxy paint.
- Brass connecting pieces.
- Required minimum flow: 6 liters / minute at 2 bar.
- Shower flow: 120 liters / min at 3 bar.
- Water inlet: screw 1-1 / 4 ".

BOCCHI emergency showers, they satisfy the specifications required by the

regulations:

Features

Marca

Categoria

Emergency shower

Price

Price

90,20 €

Without VAT

73,33 €

Product in Store

[Emergency Shower, Horizontal, With Manual](#)

- EN 15154-1. The respective standards for shower devices connected to the water system.
- EN15154-2. Respective standards for connected eye wash units to the water network.
- UNI9608, UNI10271 and DIN 12899 PART 2. Regulatory standards for eye-wash units and emergency showers.
- ANSI Z358.1-2004 (American National Standard Institute) regulatory standard of eyewash units and emergency showers.
- According to regulations the minimum eyewash flow should be 6 liters /minute and the emergency shower of 100 liters / minute: DILUVIO eye-wash flow more than 14 l/min and showers flow more than 120 l/min at 0,3 MPa.

Documents

[Technical Data Sheets - ES \(114.34 Kb\)](#)
[Installation Guide - PT \(77.8 Kb\)](#)