

SC700X Emergency Shower and Eye Wash



Description

SC700x manual emergency shower with pedestal. Full bore valve, instant automatic manual opening, closes manually.

Suitable for industries, workshops, laboratories and generally where there is a risk of fire, acids, reagents, petroleum products, radioactive materials or

any other agent.

Features:

- Product material: stainless steel
- Finish: stainless steel
- Height (mm): 2150
- Width (mm): 762
- Depth (mm): 762
- Retraction diameter (mm): 300
- Flow rate: 120 L / MIN Shower AND 14 L / MIN Eye Wash

Features

Marca

Categoria

Emergency
shower

Price

Price 1.320,27 €

Without VAT 1.073,39 €

Product in Store

[SC700X Emergency Shower and Eye Wash](#)

- Inlet valve: Inlet 1 1/4" g, female thread
- Outlet valve: Outlet 1 1/4" g, female thread

BOCCHI emergency showers and eyewashes fully comply with the specifications

requirements of the regulations:

- EN 15154-1 Standards for shower devices for the body connected to the water network and according to which the minimum flow rate of the sprayer must be at least 100 l / min. Emergency showers DILUVIO a flow rate greater than 120 l / min at 0.3 MPa.
- EN 15154-2 Standards for eyewash units connected to the water mains and according to which the minimum flow rate of the eyewash must be at least 6 l / min. DILUVIO eye drops have a flow rate of over 14 l/min at 0.3 MPa.
- UNI9608 regulations governing the use of emergency showers and eyewashes
- UNI10271 Regulations governing the use of eyewash / eyewashers
- UNI7546 / 2 UNI7546 / 3 UNI7546 / 4 which requires the presence of an individual captive cartel for the shower and another for the emergency eyewash.
- Din 12899 PART 2
- ANSI Z358.1-2004 (American National Sanitation Institute).